



Sales price 15,26 €

Base price with tax 19,95 €

Product Description Motul RBF 660 Racing Brake/Clutch Fluid (Universal)

Description

Motul RBF 660. All types of hydraulic actuated-brake and clutch systems requiring a non-silicone synthetic fluid. Specially designed to resist to high temperature of racing actuated-brake (steel or carbon) and clutch systems.

Extreme thermal resistance and stability :

The very high boiling point (**325°C**), superior to conventional DOT 5.1 non silicone base / DOT 5 silicone base fluids (260°C / 500°F mini) and DOT 4 (230°C / 446°F mini) enables an effective brake even under extreme conditions.

Efficient when rainy :

The very high wet boiling point (**205°C**) superior to conventional DOT 5.1 non-silicone base fluid (180°C / 356°F mini) and DOT 4 (155°C / 311°F mini) enables to keep an efficient brake system when rainy. Indeed, DOT 3, DOT 4 and DOT 5.1 brake fluids have the property to absorb humidity in the air, which reduces their boiling points and increases the risk to get the phenomena called " vapour lock ".

The wet boiling point is measured by humidifying the product with about 3.5 % of water.

All types of hydraulic actuated-brake and clutch systems requiring a non-silicone synthetic fluid. Specially designed to resist to high temperature of racing actuated-brake (steel or carbon) and clutch systems.

Toepasbaar op:

-Universal